



LNB KU EAGLE
ASPEN
\$1,995 MXN

ESPECIFICACIONES

Eagle Aspen 0.6 Ku Digital #770SLKu

Input	11.7-12.2 GHz
LO Frequency	950-1450 MHz
Weight	5.6 oz.
I/P Frequency	11.7-12.2 GHz
O/P Frequency	950-1450 MHz
LO Frequency	10750
Initial Setting Accuracy at 23 °C	± 500 kHz
Conversion Gain	50 to 62 dB (typical)
Gain Flatness	± 0.5 dB/24 MHz
Cross Pol. Isolation	25 dB (min.)
Image Rejection	40dB (min.)
O/P VSWR	2.0:1
O/P Power @ 1 dB Compression	0 dBm (min.)
Current Consumption	110 Ma
DC Voltage	10.5 - 21 V DC
LO Stability	(-35 °C to +52 °C) ± 2.0 MHz
LO Phase Noise(kHz offset)	-60 dBc/Hz @ 1 -80 dBc/Hz @ 10 -90 dBc/Hz @ 100
Noise Figure	0.8 dB (max.)
O/P Spurious	-60 dBm (min.)
O/P ports	1
O/P Port Type	75 W F-Female
Waveguide Interface	WR-75
Working Temperature	-35 °C to 52 °C
Humidity	0-100%

☎ 01 (744) 4 45 67 39 | 01 (744) 4 45 73 59
 contacto@antenas.mx | www.antenas.mx

 **Antenas de México**
 39 AÑOS A TU SERVICIO