



**LNB PANSAT
PK-8400
\$1,990 MXN**

ESPECIFICACIONES

Mod	PK-8400
Input Frequency	11.7 ~ 12.75 GHz
Output Frequency	950 ~ 2000MHz
L.O. Frequency	10750 + 2MHz
Noise Temp.(@ + 25'C)	0.6 to 0.9 dB Max.
Input VSWR : 2.5	1 Typ
Image Rejection	40 dBc Min.
Conversion Gain	55 dB Typ.
Output VSWR	2 : 1 Typ.
Gain Flatness	6 dBp-p Max.
Gain Ripple(@per Channel)	+/- 1.0 dB Max.
1dB Gain Compression Point	+5 dBm Max.
Output Impedanc	75 Ohms
Leakage(@ Input Port)	-60 dBm Max.
Phase Noise	-80 dBc/Hz(@ 10KHz) 95 dBc/Hz(@ 100KHz) -110 dBc/Hz(@ 1 MHz)
Power Supply	+12 to +24V DC
Requires Current	150 mA Max.
Operating Temperature	-30'C to +60'C
Storage temperature	-40'C to +80'C
Relative Humidity	0% to 95% RH
Input Waveguide flange	WR-75
IF Output Connector	F-Type Female
Weight	190g