

## CARACTERÍSTICAS

### Features & Benefits

- Zinc Die-cast Housing with Corrosion Protection
- Solde Bac
- -120 dB RF

### Specifications

	SDS-12	SDS-16
<b>Loss (dB)</b>		
5 - 40 MHz:	11	14
40 - 400 MHz:	11	14
400 - 500 MHz:	11.5	14.5
500 - 600 MHz:	12	15.5
600 - 1000 MHz:	13	15.5
<b>Isolation (dB)</b>		
5 - 40 MHz:	28	23
40 - 400 MHz:	32	28
400 - 500 MHz:	30	25
500 - 600 MHz:	28	22
600 - 1000 MHz:	25	22
<b>Return Loss Input (dB)</b>		
5 - 40 MHz:	18	18
40 - 400 MHz:	18	18
400 - 500 MHz:	18	18
500 - 600 MHz:	18	18
600 - 1000 MHz:	18	18
<b>Return Loss Output (dB)</b>		
5 - 40 MHz:	18	18
40 - 400 MHz:	20	22
400 - 500 MHz:	20	22
500 - 600 MHz:	20	20
600 - 1000 MHz:	18	18

### Ordering Information

Model	Stock No.	Description
SDS-12	1938	Splitter, 12 Way Solder Back, 5-1000 MHz
SDS-16	1939	Splitter, 16 Way Solder Back, 5-1000 MHz



SDS-16 BLONDER  
TONGUE  
\$1,995 MXN